

**Precise non-contact
temperature measurement
from -58 °F to 1922 °F**



Features:

- One of the smallest infrared sensors worldwide with up to 22:1 optical resolution
- Rugged sensing head - usable up to 356 °F ambient temperature without cooling
- Two-piece design with easy accessible programming keys and LCD backlit display
- Built-in USB interface for simple sensor setup via mobile phone or PC
- Selectable analog outputs: 0/4 – 20 mA, 0 – 5 V, 0 – 10 V, thermocouple type K
- Optional EtherNet/IP, Profinet, Ethernet TCP/IP / Modbus TCP, Modbus RTU, RS485, RS232 interface or relay outputs (2 x optically isolated)
- Easy and flexible exchange of sensing heads

General specifications

Environmental rating	IP 65 (NEMA-4)
Operating temperature range ¹⁾	-20 °C ... 180 °C (-4 °F ... 356 °F) (248 °F for LT 02) (sensing head) -20 °C ... 85 °C (-4 °F ... 185 °F) (electronics)
Storage temperature	-40 °C ... 180 °C (-40 °F ... 356 °F) (248 °F for LT 02) (sensing head) -40 °C ... 85 °C (-40 °F ... 185 °F) (electronics)
Operating air humidity range	10 – 95 %, non condensing
Vibration (sensor)	IEC 60068-2-6 (sinus shaped) IEC 60068-2-64 (broadband noise)
Shock (sensor)	IEC 60068-2-27 (25G and 50G)
Weight	40 g (1.41 oz) (sensing head) / 420 g (14.82 oz) (electronics)

Electrical Specifications

Output / analog (2x)	0 / 4 – 20 mA, 0 – 5 / 10 V, thermocouple K, alarm
Output / alarm	24 V / 50 mA (open collector)
Relay outputs (optional)	2 x 60 V DC / 42 V AC _{RMS} ; 0.4 A; optically isolated
Digital Interfaces	built-in USB-interface, Optional: EtherNet/IP, Profinet, Ethernet TCP/IP / Modbus TCP, Modbus RTU, RS485, RS232 or relay outputs (2 x optically isolated)
Output impedances	mA max. 500 Ω (with 8 – 36 V DC) mV min. 100 kΩ load impedance thermocouple 20 Ω
I/O Pins (3x)	flexible programming as in- or output: external emissivity adjustment, ambient temperature compensation, uncommitted value, trigger (reset of hold functions), alarm output (open collector 24 V / 50 mA)
Cable length	1 m (3.3 ft) (standard), 3 m (9.84 ft), 8 m (26.25ft), 15 m (49.21ft)
Power supply	8 - 30 V DC / 1.2W

Measurement specifications

Measuring Temperature range (scalable via programming keys or software / App)	-50 °C ... 650 °C [-58 °F ... 1202 °F] (LT 02) -50 °C ... 800 °C [-58 °F ... 1472 °F] (LT 15) -50 °C ... 1050 °C [-58 °F ... 1922 °F] (LT 22)
Spectral range	8 – 14 μm
Optical resolution (90% energy)	22:1 15:1 2:1
Smallest spot size	0.6 mm at 10 mm [0.02 in at 0.39 in] (LT22 + CF lens)
Measurement uncertainty ^{2), 3), 4), 5), 7)}	±1 % or ±1 °C [±1 % or ±1.8 °F]
Repeatability ^{2), 3), 4), 5), 7)}	±0.2 °C or ±0.1 % [±0.36 °F or ±0.1%] (LT02) ±0.1 °C or ±0.1 % [±0.18 °F or ±0.1%] (LT15) ±0.15 °C or ±0.1 % [±0.27 °F or ±0.1%] (LT22)
Temperature resolution (display)	0.1 K
NETD (typically) ^{4), 5), 6), 7)}	25 mK (LT 02 & LT 15) 35 mK (LT 22)
Response time (90%)	40 ms (LT02) 115 ms (LT15 & LT22)
Emissivity / Gain (adjustable via programming keys or software / App)	0.05 – 1.100
Transmissivity / Gain (adjustable via programming keys or software / App)	0.05 – 1.100
Signal processing (parameter adjustable via programming keys or software / App)	Peak hold, valley hold, average; extended hold functions with threshold and hysteresis
Software / App	Optris CompactPlus Connect / IR Mobile App

¹⁾ The LCD displays capacity may be limited at ambient temperatures below 0 °C

²⁾ Whichever is greater

³⁾ $T_{obj} > 0 °C$

⁴⁾ $\epsilon = 1$


⁵⁾ Response time = 200ms

⁶⁾ $T_{obj} = 77 °F$

⁷⁾ at ambient temperature $23 \pm 5 °C$ ($73.4 \pm 9 °F$)

S	6.5	10.9	15.2	19.6	23.9	28.3	32.6	37	41.3	45.7	50	(mm)
D	0	110	220	330	440	550	660	770	880	990	1100	(mm)

CF lens (ACCTCF)/ far field = 1.5:1



S	7	3.8	0.6	4.4	8.2	12	15.8	19.6	23.4	(mm)
D	0	5	10	15	20	25	30	35	40	(mm)

S	6.5	4.4	3.2	2.3	4.1	6.7	11.1	15.5	19.9	24.3	28.7	(mm)
D	0	25	40	50	60	75	100	125	150	175	200	(mm)



Dimensions in mm (in)



Electronics

M 12 x 1.5
(0.47 x 0.06)

23(0.91) 24(0.94)

4(0.16)

4(0.16)

89(3.5)
92(3.62)
122(4.8)

4(0.16)

70(2.76)

4(0.16)

4(0.16)

Ø4.5(0.18)

SW 12(0.47)

SW 14(0.55)

30(1.18)
16(0.63)

13(0.51)
22(0.87)
27(1.06)

optris CTi

Technical drawing of the CF optics assembly. The drawing shows a cross-section of the assembly with the following dimensions:

- 3(0.12)
- SW 14(0.55)
- 10(0.39)
- 28(1.1)
- CF optics 32 mm(1.26)
- M 12 x 1 (0.87 x 0.04)
- 14(0.55)
- 10(0.39)
- 2.8(0.11)